

FLOWPACK CRIMA



FLOW WRAPPING MACHINE

CRIMA

The new wrapping machine CRIMA can operate both in a horizontal, vertical or inclined position, using a simple handwheel located at the left of the operator.

The longitudinal sealing of the bag is made with three pairs of wheels for pulling and sealing. The traversal sealing is made by the jaws with the vertical movement.

The forming tunnel is adjustable to make the change of size in a easy and quick way.

The new CRIMA works with different types of film: polypropylene, laminated film, microperforated film, polythene etc.

The film feed speed is inverter controlled and is based on the dimensions of the product and on the type of the film.

There is no limit to the length of the bags, thanks to the PLC (Programmable Logic Controller)

The temperature of the sealing jaws and of the wheels is controlled by PLC and touch screen panel



INCLINED POSITION



Products as bread, sweets, trays.
Single product or multipack,
food or non-food products

HORIZONTAL POSITION



Products with a length more
than one meter, such as
aluminium and wooden bars.

VERTICAL POSITION



For several products:
pasta, rice, coffee, etc.

TECHNICAL FEATURES

Max. film reel width	mm	700
Min. bag dimension (H x L x W)	mm	0 x 10 x 10
Max. bag dimension (H x L x W)	mm	180 x x 300
Wrapping speed	packs / min.	10 - 25
Installed power	kW	3
Electric power supply	V - Hz	220 - 50/60
Machine dimension (H x L x W)	mm	1500 x 750 x 1200



Images and specifications are subject to continuous technological development



(A Joint Venture of Mac Due, Italy
&
Penguin Engineers, India)

ITALINDIA PACKPLUS PVT. LTD.

93, Kodayampalayam
Vaiyampalayam Post
Coimbatore - 641 110. INDIA



+91 - 422 - 650 3543 / 655 3544



info@italindia.in
sales@italindia.in



www.italindia.in